



CMS RACKING SYSTEMS

250 Maple Ave
Bird-In-Hand, PA 17505
717-397-4079 ext. 106

STAND-ALONE INSTALLATION

1



Secure the upright to the base using 4 nuts and 4 bolts. Repeat for multiple uprights if applicable.

2



Install two crossbraces using 6 bolts and nuts (6 per cross brace) to connect uprights. Adjust to the preferred upright centers. Repeat for multiple uprights if applicable.

3




Attach arms by sliding the hook into the desired spaces on the upright to securely lock arms in place.

BACK TO BACK SETUP



UPRIGHT ONLY KIT



STARTER KIT

ADD-ON KIT

OPTIONAL ARM STOPS



Insert arm stops to keep items from rolling off the shelf.

OPTIONAL SHELVING



Install shelving using pre-drilled holes for plywood or CMS aluminium shelves.

WALL-MOUNT INSTALLATION

1



Determine first upright position. Then measure subsequent centers and mark

2



Mark and screw in.

3



Attach arms by sliding the hook into the desired spaces on the upright to securely lock arms in place.



IMPORTANT:

Be sure to fasten to a solid wall structure. Weight limits vary depending on wall construction.

WALLMOUNT




HEIGHT—30 in



RACKING SYSTEMS

STANDALONE



HEIGHT—6 ft or 8 ft

- 12 in, 18 in, or 24 in ARMS, 6" ADJUSTMENT
- 200 LBS/ARM
- 1000 LBS/UPRIGHT (STAND-ALONE UNIT)
- POWDERCOATED STEEL



VERSATILE STORAGE

Great for versatile garage storage! Use your own plywood for sturdy, economic shelving or CMS aluminum shelves.

Adjustable crossbraces allow for **32", 36", 40", 48", 52", 56", 60"** centers.



CONFIGURATIONS

The customization of CMS Racking allows configurations including **back-to-back racking**.



Closer spacing between uprights accommodates more weight.




MIXED-USE






Excellent for mixed use warehousing or retail displays for both cantilever storage and shelving!

CMS aluminum shelves are best for **32" or 48"** centers, available in **4' or 8' length**.

	STAND ALONE 8'	STAND ALONE 6'	WALL MOUNT 30"
	- Upright Max 1000 lbs - Arm max 200 lbs each - 32" - 60" adjustment every 4"		- Upright Max depends on wall construction and installation - Arm max 200 lbs each
STARTER KIT	- 2 uprights - 10 ct arms 12" 18" 24" - 2 adjustable cross braces - Fasteners 		- 2 uprights - 6 ct arms 12" 18" 24" - Fasteners 
ADD-ON KIT	- 1 upright + 1 base - 5 ct arms 12" 18" 24" - 2 adjustable cross braces - Fasteners 		- 1 upright - 3 ct arms 12" 18" 24" - Fasteners  <div>Extendable! Add another upright to double your height!</div>
UPRIGHT ONLY KIT	- 1 upright + 1 base - 5 ct arms 12" 18" 24" - Fasteners 		



Base fasteners included with stand alone kits



4' Aluminum Shelves
Starter Shelf

2805-12x48
12" x 48" x 4"
2805-18x48
18" x 48" x 4"
2805-24x48
24" x 48" x 4"



8' Aluminum Shelves
Recommended use on 32" or 48" centers

2805-12x96
12" x 96" x 4"
2805-18x96
18" x 96" x 4"
2805-24x96
24" x 96" x 4"



2805-STOP
Arm Stop
1" x 5" x 3/4"

